

المميزات الفنية

رقم الجزء	النوع	الموصل			العازل		O.D.		اقصى حد للمقاومة الخارجية 20 °C الى (Ω.Km)	الحد الادنى لمقاومة العازل at 70 °C (Ω.cm)	الجهد (V)
		الحجم mm ²	رقم الكابل /m m	O.D. mm	السماكة mm	O.D. mm	الشكلي O.D. mm	الحد الاقصى O.D. mm			
200AVS0003	AVS	0.3	7/0.26	0.8	0.5	0.32	1.8	1.9	50.2	109	1000
200AVS0005		0.5	7/0.32	1	0.5	0.32	2	2.1	32.7		
200AVS0008 516		0.85	16/0.26	1.2	0.5	0.32	2.2	2.3	22		
200AVS0085 11			11/0.32	1.2	0.5	0.32	2.2	2.3	20.8		
200AVS0012 5		1.25	16/0.32	1.5	0.5	0.32	2.5	2.6	14.3		
200AVS002		2	26/0.32	1.9	0.5	0.32	2.9	3.1	8.81		
200AVS003		3	41/0.32	2.4	0.6	0.4	3.6	3.8	5.59		
200AVS005		5	65/0.32	3	0.7	0.48	4.4	4.6	3.52		
200AVS0003 F		0.3f	15/0.18	0.8	0.5	0.32	1.8	1.9	48.9		
200AVS0005 F		0.5f	20/0.18	1	0.5	0.32	2	2.1	36.7		
200AVS0007 5F		0.75f	30/0.18	1.2	0.5	0.32	2.2	2.3	24.4		
200AVS0001 25F		1.25f	50/0.18	1.5	0.5	0.32	2.5	2.6	14.7		
200AVS002F		2.0f	37/0.26	1.9	0.5	0.32	2.9	3.1	9.5		
200AVSS000 3	AVSS	0.3	7/0.26	0.8	0.3	0.24	1.4	1.5	50.2	109	1000
200AVSS000 5		0.5	7/0.32	1	0.3	0.24	1.6	1.7	32.7		
200AVSS000 8519		0.85	19/0.24	1.2	0.3	0.24	1.8	1.9	21.7		
200AVSS000 857			7/0.40	1.1	0.3	0.24	1.8	1.9	20.8		
200AVSS001 25		1.25	19/0.29	1.5	0.3	0.24	2.1	2.2	14.9		
200AVSS002		2	19/0.37	1.9	0.4	0.32	2.7	2.8	9		
200AVSS003 F		0.3f	19/0.16	0.8	0.3	0.24	1.4	1.5	48.8		
200AVSS005 F		0.5f	19/0.19	1	3	0.24	1.6	1.7	34.6		

200AVSS000 75F		0.75f	19/0.23	1.2	0.3	0.24	1.8	1.9	23.6		
200AVSS000 125F		1.25f	37/0.21	1.5	0.3	0.24	2.1	2.2	14.6		
200AVSS002 F		2.0f	37/0.26	1.8	0.4	0.32	2.6	2.7	9.5		