

الجزء رقم	الموصل			الاقطاب	العازل		لولبي		الغمد		اكثر مقاومة للموصل Ω/km	اقل مقاومة للموصل M Ω .Km	الفولتاج V
	AWG	رقم ./mm	O.D. mm		السلك الرمزي مم	الرمزي O.D. mm	AI	الجدل	السلك الرمزي مم	الرمزي O.D.			
									mm	mm			
1001251700 3028	28	7/0.127	0.38	3	0.23	0.88	100%	85%	0.80	3.70	223.75	10	1500
1001251700 4028				4			100%	85%		3.90			
1001251700 5028				5			100%	85%		4.20			
1001251700 6028				6			100%	85%		4.50			
1001251700 7028				7			100%	85%		4.50			
1001251700 8028				8			100%	85%		4.80			
1001251700 9028				9			100%	85%		5.10			
1001251701 0028				10			100%	85%		5.30			
10012517011 028				11			100%	85%		5.40			
1001251701 2028				12			100%	85%		5.40			
1001251701 3028				13			100%	85%		5.70			
1001251701 4028				14			100%	85%		5.70			
1001251701 5028				15			100%	85%		5.90			
1001251702 5028				25			100%	85%	1.00	7.60			
1001251703 7028				37			100%	85%		8.30			
1001251705 0028				50			100%	85%		9.60			
1001251700 2026	26	7/0.16	0.48	2	0.25	0.98	100%	85%	0.80	3.70	139.33		
1001251700 3026				3			100%	85%		3.90			
1001251700 4026				4			100%	85%		4.20			
1001251700 5026				5			100%	85%		4.50			
1001251700 6026				6			100%	85%		4.80			

1001251700 7026				7			100%	85%		4.80			
1001251700 8026				8			100%	85%		5.10			
1001251700 9026				9			100%	85%		5.50			
1001251701 0026				10			100%	85%		5.80			
10012517011 026				11			100%	85%		5.90			
1001251701 2026				12			100%	85%		5.90			
1001251701 3026				13			100%	85%		6.20			
1001251701 4026				14			100%	85%		6.20			
1001251701 5026				15			100%	85%		6.50			
1001251702 5026				25			100%	85%	1.00	8.30			
1001251703 7026				37			100%			9.20			
1001251705 0026				50			100%			10.60			
1001251700 2024	24	11/0.16	0.16	2	0.23	1.11	100%		0.80	4.00	93.3		
1001251700 3024				3			100%			4.20			
1001251700 4024				4			100%			4.50			
1001251700 5024				5			100%			4.80			
1001251700 6024				6			100%		0.90	5.10			
1001251700 7024				7			100%			5.10			
1001251700 8024				8			100%			5.14			
1001251700 9024				9			100%			6.00			
1001251701 0024				10			100%			6.40			
10012517011 024				11			100%			6.60			

1001251701 2024				12			100%			6.60		10	1500
1001251701 3024				13			100%			6.80			
1001251701 4024				14			100%			6.80			
1001251701 5024				15						7.20			
1001251702 5024				25					1.00	8.90			
1001251703 7024				37						9.90			
1001251705 0024				50						11.40			
1001251700 2022	22	17/0.16	0.76	2	0.23	1.26			0.90	4.40	55.0		
1001251700 3022				3						4.60			
1001251700 4022				4						4.80			
1001251700 5022				5						5.20			
1001251700 6022				6					1.00	5.60			
1001251700 7022				7						5.60			
1001251700 8022				8						6.20			
1001251700 9022				9						6.70			
1001251701 0022				10			100%	85%		7.10			
10012517011 022				11			100%	85%		7.50			
1001251701 2022				12			100%	85%		7.50			
1001251701 3022				13			100%	85%		7.80			
1001251701 4022				14			100%	85%		7.80			
1001251701 5022				15			100%	85%		8.20			
1001251702 5022				25			100%	85%	1.10	10.40			

1001251703 7022				37			100%	85%		11.50			
1001251705 0022				50			100%	85%		13.30			