

**Parámetros**

| Partes No.         | Tipo | Conductor         |                   |            | Aislamiento  |            | O.D.                  |                      | Resistencia<br>máx. al<br>exterior en<br>20 °C<br>(Ω.Km) | Resistencia<br>de<br>aislamiento<br>mínima<br>en 70 °C<br>(Ω.cm) | Tensi<br>ón<br>(V) |
|--------------------|------|-------------------|-------------------|------------|--------------|------------|-----------------------|----------------------|----------------------------------------------------------|------------------------------------------------------------------|--------------------|
|                    |      | Tama<br>ño<br>mm² | Alambre<br>No./mm | O.D.<br>mm | Grosor<br>mm | O.D.<br>mm | Nominal<br>O.D.<br>mm | Máximo<br>O.D.<br>mm |                                                          |                                                                  |                    |
| 200AVS0003         | AVS  | 0.3               | 7/0.26            | 0.8        | 0.5          | 0.32       | 1.8                   | 1.9                  | 50.2                                                     | 109                                                              | 1000               |
| 200AVS0005         |      | 0.5               | 7/0.32            | 1          | 0.5          | 0.32       | 2                     | 2.1                  | 32.7                                                     |                                                                  |                    |
| 200AVS0008<br>516  |      | 0.85              | 16/0.26           | 1.2        | 0.5          | 0.32       | 2.2                   | 2.3                  | 22                                                       |                                                                  |                    |
| 200AVS0085<br>11   |      |                   | 11/0.32           | 1.2        | 0.5          | 0.32       | 2.2                   | 2.3                  | 20.8                                                     |                                                                  |                    |
| 200AVS0012<br>5    |      | 1.25              | 16/0.32           | 1.5        | 0.5          | 0.32       | 2.5                   | 2.6                  | 14.3                                                     |                                                                  |                    |
| 200AVS002          |      | 2                 | 26/0.32           | 1.9        | 0.5          | 0.32       | 2.9                   | 3.1                  | 8.81                                                     |                                                                  |                    |
| 200AVS003          |      | 3                 | 41/0.32           | 2.4        | 0.6          | 0.4        | 3.6                   | 3.8                  | 5.59                                                     |                                                                  |                    |
| 200AVS005          |      | 5                 | 65/0.32           | 3          | 0.7          | 0.48       | 4.4                   | 4.6                  | 3.52                                                     |                                                                  |                    |
| 200AVS0003<br>F    |      | 0.3f              | 15/0.18           | 0.8        | 0.5          | 0.32       | 1.8                   | 1.9                  | 48.9                                                     |                                                                  |                    |
| 200AVS0005<br>F    |      | 0.5f              | 20/0.18           | 1          | 0.5          | 0.32       | 2                     | 2.1                  | 36.7                                                     |                                                                  |                    |
| 200AVS0007<br>5F   |      | 0.75f             | 30/0.18           | 1.2        | 0.5          | 0.32       | 2.2                   | 2.3                  | 24.4                                                     |                                                                  |                    |
| 200AVS0001<br>25F  |      | 1.25f             | 50/0.18           | 1.5        | 0.5          | 0.32       | 2.5                   | 2.6                  | 14.7                                                     |                                                                  |                    |
| 200AVS002F         |      | 2.0f              | 37/0.26           | 1.9        | 0.5          | 0.32       | 2.9                   | 3.1                  | 9.5                                                      |                                                                  |                    |
| 200AVSS000<br>3    | AVSS | 0.3               | 7/0.26            | 0.8        | 0.3          | 0.24       | 1.4                   | 1.5                  | 50.2                                                     | 109                                                              | 1000               |
| 200AVSS000<br>5    |      | 0.5               | 7/0.32            | 1          | 0.3          | 0.24       | 1.6                   | 1.7                  | 32.7                                                     |                                                                  |                    |
| 200AVSS000<br>8519 |      | 0.85              | 19/0.24           | 1.2        | 0.3          | 0.24       | 1.8                   | 1.9                  | 21.7                                                     |                                                                  |                    |
| 200AVSS000<br>857  |      |                   | 7/0.40            | 1.1        | 0.3          | 0.24       | 1.8                   | 1.9                  | 20.8                                                     |                                                                  |                    |
| 200AVSS001<br>25   |      | 1.25              | 19/0.29           | 1.5        | 0.3          | 0.24       | 2.1                   | 2.2                  | 14.9                                                     |                                                                  |                    |
| 200AVSS002         |      | 2                 | 19/0.37           | 1.9        | 0.4          | 0.32       | 2.7                   | 2.8                  | 9                                                        |                                                                  |                    |
| 200AVSS003<br>F    |      | 0.3f              | 19/0.16           | 0.8        | 0.3          | 0.24       | 1.4                   | 1.5                  | 48.8                                                     |                                                                  |                    |
| 200AVSS005<br>F    |      | 0.5f              | 19/0.19           | 1          | 3            | 0.24       | 1.6                   | 1.7                  | 34.6                                                     |                                                                  |                    |
| 200AVSS000         |      | 0.75f             | 19/0.23           | 1.2        | 0.3          | 0.24       | 1.8                   | 1.9                  | 23.6                                                     |                                                                  |                    |

|                    |  |       |         |     |     |      |     |     |      |  |  |
|--------------------|--|-------|---------|-----|-----|------|-----|-----|------|--|--|
| 75F                |  |       |         |     |     |      |     |     |      |  |  |
| 200AVSS000<br>125F |  | 1.25f | 37/0.21 | 1.5 | 0.3 | 0.24 | 2.1 | 2.2 | 14.6 |  |  |
| 200AVSS002<br>F    |  | 2.0f  | 37/0.26 | 1.8 | 0.4 | 0.32 | 2.6 | 2.7 | 9.5  |  |  |