

Especificaciones

Parte No.	AWG	Conductor No/mm	Grosor de aislamiento (mm)	Aislamiento O.D. (mm)	Peso del cable (kg/km)
1001THW014	14	1/1.628	1.14	4.1	20
1001THW012	12	1/2.054	1.14	4.4	25
1001THW010	10	1/2.59	1.14	5.1	35
1001THW08	8	1/3.27	1.53	6.9	50
1001THW014S	14	7/0.62	1.14	4.4	20
1001THW012S	12	7/0.78	1.14	4.9	25
1001THW010S	10	7/0.98	1.14	5.4	35
1001THW08S	8	7/1.24	1.14	6.9	50
1001THW06	6	7/1.56	1.14	7.7	65
1001THW04	4	7/1.97	1.14	8.9	85
1001THW02	2	7/2.48	1.53	10.5	115
1001THW01	1	19/1.64	2.03	12.5	130
1001THW0101	1/0	19/1.84	2.03	13.5	150
1001THW0102	2/0	19/2.13	2.03	14.5	175
1001THW0103	3/0	19/2.39	2.03	15.8	200
1001THW0104	4/0	19/2.68	2.03	17.3	230
1001THW0250	250	37/2.092	2.42	19.1	255
1001THW0300	300	37/2.29	2.42	20.6	285
1001THW0350	350	37/2.48	2.42	21.9	310
1001THW0400	400	37/2.644	2.42	22.9	335
1001THW0500	500	37/2.952	2.42	24.9	380
1001THW0600	600	61/2.52	2.8	27.7	420
1001THW0750	750	61/2.818	2.8	30.23	475
1001THW01000	1000	61/3.254	2.8	34.1	545