

Especificaciones

Part No.	Tipo de Conductor	Conductor			Aislamiento		Resistencia del conductor	Resistencia de aislamiento	Resistencia de voltaje
		AWG	Cable No./mm	O.D. mm	Grosor mm	O.D. mm	Máx Ω /km	Mín M Ω .Km	V
1001100732	Trenzado	32	7/0.08	0.244	0.38	1.00	564.49	15	2000
1001100730		30	7/0.10	0.30	0.38	1.12	354.24		
1001100728		28	7/0.127	0.38	0.38	1.20	223.75		
1001100726		26	7/0.16	0.48	0.38	1.30	139.73		
1001100724		24	11/0.16	0.61	0.38	1.43	93.3		
1001100722		22	17/0.16	0.76	0.38	1.58	55.0		
1001100720		20	26/0.16	0.94	0.38	1.76	34.6		
1001100718		18	41/0.16	1.18	0.38	2.05	21.8		
1001100716		16	26/0.254	1.49	0.38	2.40	13.7		
1001100728S1	Sólido	28	1/0.32	0.32	0.38	1.14	227.39		
1001100726S1		26	1/0.404	0.404	0.38	1.22	142.79		
1001100724S1		24	1/0.511	0.511	0.38	1.33	89.39		
1001100722S1		22	1/0.643	0.643	0.38	1.46	54.3		
1001100720S1		20	1/0.813	0.813	0.38	1.63	33.9		
1001100718S1		18	1/1.024	1.024	0.38	1.84	21.4		
1001100716S1		16	1/1.29	1.29	0.38	2.11	13.5		