

Especificaciones

Part No.	Tipo de conductor	Conductor			Aislamiento		Resistencia del conductor Máx (Ω/km)	Resistencia de aislamiento o Min. (M Ω .km)	Resistencia de voltaje (V)
		AWG	Cable No./mm	O.D. (mm)	Grosor (mm)	O.D. (mm)			
100110239030	Trenzado	30	7/0.10	0.30	0.76	1.82	354.24	15	3000
100110239028		28	7/0.127	0.38	0.76	1.9	223.75		
100110239026		26	7/0.16	0.48	0.76	2.0	139.73		
100110239024		24	11/0.16	0.61	0.76	2.13	93.3		
100110239022		22	17/0.16	0.76	0.76	2.28	55.0		
100110239020		20	26/0.16	0.94	0.76	2.47	34.6		
100110239018		18	41/0.16	1.18	0.76	2.7	21.8		
100110239016		16	26/0.254	1.49	0.76	3.01	13.7		
100110239014		14	41/0.254	1.88	0.76	3.4	8.62		
100110239012		12	65/0.254	2.37	0.76	3.89	5.43		
100110239010		10	105/0.254	3.40	0.76	4.92	3.41		
100110239030S1	Sólido	30	1/0.254	0.25	0.76	1.77	354.24	15	3000
100110239028S1		28	1/0.32	0.32	0.76	1.84	223.75		
100110239026S1		26	1/0.404	0.404	0.76	1.92	139.73		
100110239024S1		24	1/0.511	0.511	0.76	2.03	93.3		
100110239022S1		22	1/0.643	0.643	0.76	2.16	55.0		
100110239020S1		20	1/0.813	0.813	0.76	2.33	34.6		
100110239018S1		18	1/1.02	1.02	0.76	2.54	21.8		
100110239016S1		16	1/1.29	1.29	0.76	2.81	13.7		