

Parte No.	Núcleos	Conductor		Aislamiento		Blindaje	Funda	Cable	Resistencia del conductor a 20°C
		AWG	No/mm	Grosor mm	O.D. mm	Cubierta %	Grosor mm	O.D. mm	Ω/km
100120233002030	2	30	7/0.100	0.23	0.80	85	0.76	3.60	381.00
100120233002028		28	7/0.127	0.23	0.90	85	0.76	3.90	239.00
100120233002026		26	7/0.16	0.23	1.00	85	0.76	4.00	150.00
100120233002024		24	11/0.16	0.23	1.10	85	0.76	4.20	94.20
100120233002022		22	17/0.16	0.23	1.30	85	0.76	4.60	59.40
100120233002020		20	21/0.178	0.23	1.50	85	0.76	5.00	36.70
100120233002018		18	34/0.178	0.23	1.80	85	0.76	5.60	23.20
100120233002016		16	26/0.25	0.23	2.00	85	0.76	7.80	14.60
100120233003030	3	30	7/0.100	0.23	0.80	85	0.76	5.50	381.00
100120233003028		28	7/0.127	0.23	0.90	85	0.76	5.70	239.00
100120233003026		26	7/0.16	0.23	1.00	85	0.76	5.90	150.00
100120233003024		24	11/0.16	0.23	1.10	85	0.76	6.10	94.20
100120233003022		22	17/0.16	0.23	1.30	85	0.76	6.50	59.40
100120233003020		20	21/0.178	0.23	1.50	85	0.76	7.00	36.70
100120233003018		18	34/0.178	0.23	1.80	85	0.76	7.60	23.20
100120233004030	4	30	7/0.100	0.23	0.80	85	0.76	5.70	381.00
100120233004028		28	7/0.127	0.23	0.90	85	0.76	5.90	239.00
100120233004026		26	7/0.16	0.23	1.00	85	0.76	6.20	150.00
100120233004024		24	11/0.16	0.23	1.10	85	0.76	6.50	94.20
100120233004022		22	17/0.16	0.23	1.30	85	0.76	6.90	59.40
100120233004020		20	21/0.178	0.23	1.50	85	0.76	7.40	36.70
100120233005030	5	30	7/0.100	0.23	0.80	85	0.76	6.00	281.00

030									
100120233005 028		28	7/0.127	0.23	0.90	85	0.76	6.30	239.00
100120233005 026		26	7/0.16	0.23	1.00	85	0.76	6.40	150.00
100120233005 024		24	11/0.16	0.23	1.10	85	0.76	6.80	94.20
100120233005 022		22	17/0.16	0.23	1.30	85	0.76	7.40	59.40
100120233006 030	6	30	7/0.100	0.23	0.80	85	0.76	6.40	381.00
100120233006 028		28	7/0.127	0.23	0.90	85	0.76	6.70	239.00
100120233006 026		26	7/0.16	0.23	1.00	85	0.76	7.00	150.00
100120233006 024		24	11/0.16	0.23	1.10	85	0.76	7.30	94.20