

Parte No.	Núcleos	Conductor		Grosor de aislamiento mm	Aislamiento O.D. mm	Cobertura del blindaje %	Grosor de la funda mm	Cable O.D. mm	Resistencia del conductor a 20°C (Ω/km)
		AWG	No./mm						
100120234002030	2	30	7/0.100	0.76	1.90	85	1.15	6.20	381.00
100120234002028		28	7/0.127	0.76	2.00	85	1.15	6.40	239.00
100120234002026		26	7/0.16	0.76	2.10	85	1.15	6.60	150.00
100120234002024		24	11/0.16	0.76	2.20	85	1.15	6.80	94.20
100120234002022		22	17/0.16	0.76	2.40	85	1.15	7.20	59.40
100120234002020		20	21/0.178	0.76	2.50	85	1.15	7.40	36.70
100120234002018		18	34/0.178	0.76	2.80	85	1.15	8.00	23.20
100120234002016		16	26/0.25	0.76	3.10	85	1.15	8.50	14.60
100120234003030	3	30	7/0.100	0.76	1.90	85	1.15	6.40	381.00
100120234003028		28	7/0.127	0.76	2.00	85	1.15	6.60	239.00
100120234003026		26	7/0.16	0.76	2.10	85	1.15	6.80	150.00
100120234003024		24	11/0.16	0.76	2.20	85	1.15	7.00	94.20
100120234003022		22	17/0.16	0.76	2.40	85	1.15	7.60	59.40
100120234003020		20	21/0.178	0.76	2.50	85	1.15	7.80	36.70
100120234003018		18	34/0.178	0.76	2.80	85	1.15	8.50	23.20
100120234004030	4	30	7/0.100	0.76	1.90	85	1.15	7.00	381.00
100120234004028		28	7/0.127	0.76	2.00	85	1.15	7.20	239.00
100120234004026		26	7/0.16	0.76	2.10	85	1.15	7.40	150.00
100120234004024		24	11/0.16	0.76	2.20	85	1.15	7.60	94.20
100120234004022		22	17/0.16	0.76	2.40	85	1.15	8.20	59.40

22									
1001202340040 20		20	21/0.17 8	0.76	2.50	85	1.15	8.50	36.70
1001202340050 30	5	30	7/0.100	0.76	1.90	85	1.15	7.60	381.00
1001202340050 28		28	7/0.127	0.76	2.00	85	1.15	7.80	239.00
1001202340050 26		26	7/0.16	0.76	2.10	85	1.15	8.00	150.00
1001202340050 24		24	11/0.16	0.76	2.20	85	1.15	8.40	94.20
1001202340050 22		22	17/0.16	0.76	2.40	85	1.15	8.80	59.40
1001202340060 30	6	30	7/0.100	0.76	1.90	85	1.15	8.00	381.00
1001202340060 28		28	7/0.127	0.76	2.00	85	1.15	8.40	239.00
1001202340060 26		26	7/0.16	0.76	2.10	85	1.15	8.60	150.00
1001202340060 24		24	11/0.16	0.76	2.20	85	1.15	9.00	94.20