

Especificaciones

Parte No.	Núcleos	Conductor			Aislamiento		Forro		O.D.	
		AWG	Nº./mm	O.D. (mm)	Grosor (mm)	O.D. (mm)	Grosor máximo (mm)	Grosor mínimo (mm)	Máx. O.D. (mm)	Mín. O.D. (mm)
10012586002026	2	26	7/0.16	0.48	0.76	2.00	0.76	0.61	5.92	5.62
10012586002024	2	24	11/0.16	0.61	0.76	2.13	0.76	0.61	6.18	5.88
10012586002022	2	22	17/0.16	0.76	0.76	2.28	0.76	0.61	6.48	6.18
10012586002020	2	20	26/0.16	0.95	0.76	2.47	0.76	0.61	6.86	6.56
10012586002018	2	18	41/0.16	1.44	0.76	2.76	0.76	0.61	7.04	6.74
10012586002016	2	16	26/0.254	1.84	0.76	3.07	0.76	0.61	7.66	7.36
10012586002014	2	14	41/0.254	2.29	0.76	3.46	0.76	0.61	8.44	8.14
10012586002012	2	12	65/0.254	3.05	0.76	3.95	0.76	0.61	9.42	9.12
10012586002010	2	10	105/0.254	3.6	0.76	5.00	0.76	0.61	11.52	11.22
10012586002008	2	8	168/0.254	4.6	1.15	6.6	0.76	0.61	14.72	14.22
10012586003026	3	26	7/0.16	0.48	0.76	2.00	0.76	0.61	5.92	5.62
10012586003024	3	24	11/0.16	0.61	0.76	2.13	0.76	0.61	6.18	5.88
10012586003022	3	22	17/0.16	0.76	0.76	2.28	0.76	0.61	6.48	6.18
10012586003020	3	20	26/0.16	0.95	0.76	2.47	0.76	0.61	6.86	6.56
10012586003018	3	18	41/0.16	1.44	0.76	2.76	0.76	0.61	7.47	7.17
10012586003016	3	16	26/0.254	1.84	0.76	3.07	0.76	0.61	8.14	7.84
10012586003014	3	14	41/0.254	2.29	0.76	3.46	0.76	0.61	8.98	8.68
10012586003012	3	12	65/0.254	3.05	0.76	3.95	0.76	0.61	10.03	9.78
10012586003010	3	10	105/0.254	3.6	0.76	5.00	0.76	0.61	12.19	11.99

10012586003008	3	8	168/0.254	4.6	1.15	6.6	0.76	0.61	15.74	15.44
10012586004028	4	28	7/0.127	0.38	0.76	1.90	0.76	0.61	6.30	6.00
10012586004026	4	26	7/0.16	0.48	0.76	2.00	0.76	0.61	6.54	6.24
10012586004024	4	24	11/0.16	0.61	0.76	2.13	0.76	0.61	6.67	6.37
10012586004022	4	22	17/0.16	0.76	0.76	2.28	0.76	0.61	7.04	6.74
10012586004020	4	20	26/0.16	0.95	0.76	2.47	0.76	0.61	7.49	7.19
10012586004018	4	18	41/0.16	1.44	0.76	2.76	0.76	0.61	8.19	7.89
10012586004016	4	16	26/0.254	1.84	0.76	3.07	0.76	0.61	8.94	8.64
10012586004014	4	14	41/0.254	2.29	0.76	3.46	0.76	0.61	9.87	9.58
10012586004012	4	12	65/0.254	3.05	0.76	3.95	0.76	0.61	11.1	10.8
10012586004010	4	10	105/0.254	3.6	0.76	5.00	0.76	0.61	13.59	13.29
10012586004008	4	8	168/0.254	4.6	1.15	6.6	0.76	0.61	17.46	17.16
10012586005028	5	28	7/0.127	0.38	0.76	1.90	0.76	0.61	6.82	6.52
10012586005026	5	26	7/0.16	0.48	0.76	2.00	0.76	0.61	7.08	6.78
10012586005024	5	24	11/0.16	0.61	0.76	2.13	0.76	0.61	7.28	6.98
10012586005022	5	22	17/0.16	0.76	0.76	2.28	0.76	0.61	7.68	7.38
10012586005020	5	20	26/0.16	0.95	0.76	2.47	0.76	0.61	8.19	7.89
10012586005018	5	18	41/0.16	1.44	0.76	2.76	0.76	0.61	8.98	8.68
10012586005016	5	16	26/0.254	1.84	0.76	3.07	0.76	0.61	9.81	9.51
10012586005014	5	14	41/0.254	2.29	0.76	3.46	0.76	0.61	10.87	10.57
10012586005012	5	12	65/0.254	3.05	0.76	3.95	0.76	0.61	12.19	11.89
10012586005010	5	10	105/0.254	3.6	0.76	5.00	0.76	0.61	15.02	14.72

100125860050 08	5	8	168/0.2 54	4.6	1.15	6.6	0.76	0.61	19.34	19.04
100125860060 28	6	28	7/0.127	0.38	0.76	1.90	0.76	0.61	7.29	6.99
100125860060 26	6	26	7/0.16	0.48	0.76	2.00	0.76	0.61	7.57	7.27
100125860060 24	6	24	11/0.16	0.61	0.76	2.13	0.76	0.61	7.91	7.61
100125860060 22	6	22	17/0.16	0.76	0.76	2.28	0.76	0.61	8.36	8.06