

Especificaciones

Parte No.	Conductor				Aislamiento		Forro		O.D.	
	Núcleos	AWG	N0./mm	O.D. (mm)	Grosor(mm)	O.D. (mm)	Grosor máximo (mm)	Grosor mínimo (mm)	Max. (mm)	Min. (mm)
10012587002026	2	26	7/0.16	0.48	0.76	2.00	0.76	0.61	5.92	5.62
10012587002024	2	24	11/0.16	0.61	0.76	2.13	0.76	0.61	6.18	5.88
10012587002022	2	22	17/0.16	0.76	0.76	2.28	0.76	0.61	6.48	6.18
10012587002020	2	20	26/0.16	0.95	0.76	2.47	0.76	0.61	6.86	6.56
10012587002018	2	18	41/0.16	1.44	0.76	2.76	0.76	0.61	7.04	6.74
10012587002016	2	16	26/0.254	1.84	0.76	3.07	0.76	0.61	7.66	7.36
10012587002014	2	14	41/0.254	2.29	0.76	3.46	0.76	0.61	8.44	8.14
10012587002012	2	12	65/0.254	3.05	0.76	3.95	0.76	0.61	9.42	9.12
10012587002010	2	10	105/0.254	3.6	0.76	5.00	0.76	0.61	11.52	11.22
10012587002008	2	8	168/0.254	4.6	1.15	6.6	0.76	0.61	14.72	14.22
10012587003026	3	26	7/0.16	0.48	0.76	2.00	0.76	0.61	5.92	5.62
10012587003024	3	24	11/0.16	0.61	0.76	2.13	0.76	0.61	6.18	5.88
10012587003022	3	22	17/0.16	0.76	0.76	2.28	0.76	0.61	6.48	6.18
10012587003020	3	20	26/0.16	0.95	0.76	2.47	0.76	0.61	6.86	6.56
10012587003018	3	18	41/0.16	1.44	0.76	2.76	0.76	0.61	7.47	7.17
10012587003016	3	16	26/0.254	1.84	0.76	3.07	0.76	0.61	8.14	7.84
10012587003014	3	14	41/0.254	2.29	0.76	3.46	0.76	0.61	8.98	8.68
10012587003012	3	12	65/0.254	3.05	0.76	3.95	0.76	0.61	10.03	9.78
10012587003010	3	10	105/0.254	3.6	0.76	5.00	0.76	0.61	12.19	11.99
10012587003008	3	8	168/0.254	4.6	1.15	6.6	0.76	0.61	15.74	15.44
10012587004028	4	28	7/0.127	0.38	0.76	1.90	0.76	0.61	6.30	6.00
10012587004026	4	26	7/0.16	0.48	0.76	2.00	0.76	0.61	6.54	6.24
10012587004024	4	24	11/0.16	0.61	0.76	2.13	0.76	0.61	6.67	6.37
10012587004022	4	22	17/0.16	0.76	0.76	2.28	0.76	0.61	7.04	6.74
10012587004020	4	20	26/0.16	0.95	0.76	2.47	0.76	0.61	7.49	7.19
10012587004018	4	18	41/0.16	1.44	0.76	2.76	0.76	0.61	8.19	7.89
10012587004016	4	16	26/0.254	1.84	0.76	3.07	0.76	0.61	8.94	8.64
10012587004014	4	14	41/0.254	2.29	0.76	3.46	0.76	0.61	9.87	9.58
10012587004012	4	12	65/0.254	3.05	0.76	3.95	0.76	0.61	11.1	10.8
10012587004010	4	10	105/0.254	3.6	0.76	5.00	0.76	0.61	13.59	13.29

10012587004008	4	8	168/0.25 4	4.6	1.15	6.6	0.76	0.61	17.46	17.16
10012587005028	5	28	7/0.127	0.38	0.76	1.90	0.76	0.61	6.82	6.52
10012587005026	5	26	7/0.16	0.48	0.76	2.00	0.76	0.61	7.08	6.78
10012587005024	5	24	11/0.16	0.61	0.76	2.13	0.76	0.61	7.28	6.98
10012587005022	5	22	17/0.16	0.76	0.76	2.28	0.76	0.61	7.68	7.38
10012587005020	5	20	26/0.16	0.95	0.76	2.47	0.76	0.61	8.19	7.89
10012587005018	5	18	41/0.16	1.44	0.76	2.76	0.76	0.61	8.98	8.68
10012587005016	5	16	26/0.254	1.84	0.76	3.07	0.76	0.61	9.81	9.51
10012587005014	5	14	41/0.254	2.29	0.76	3.46	0.76	0.61	10.87	10.57
10012587005012	5	12	65/0.254	3.05	0.76	3.95	0.76	0.61	12.19	11.89
10012587005010	5	10	105/0.25 4	3.6	0.76	5.00	0.76	0.61	15.02	14.72
10012587005008	5	8	168/0.25 4	4.6	1.15	6.6	0.76	0.61	19.34	19.04
10012587006028	6	28	7/0.127	0.38	0.76	1.90	0.76	0.61	7.29	6.99
10012587006026	6	26	7/0.16	0.48	0.76	2.00	0.76	0.61	7.57	7.27
10012587006024	6	24	11/0.16	0.61	0.76	2.13	0.76	0.61	7.91	7.61
10012587006022	6	22	17/0.16	0.76	0.76	2.28	0.76	0.61	8.36	8.06
10012587006020	6	20	26/0.16	0.95	0.76	2.47	0.76	0.61	8.93	8.63
10012587006018	6	18	41/0.16	1.44	0.76	2.76	0.76	0.61	9.8	9.5
10012587006016	6	16	26/0.254	1.84	0.76	3.07	0.76	0.61	10.73	10.43
10012587006014	6	14	41/0.254	2.29	0.76	3.46	0.76	0.61	11.9	11.6
10012587006012	6	12	65/0.254	3.05	0.76	3.95	0.76	0.61	13.37	13.07
10012587006010	6	10	105/0.25 4	3.6	0.76	5.00	0.76	0.61	16.52	16.22
10012587006008	6	8	168/0.25 4	4.6	1.15	6.6	1.53	1.22	22.86	22.24
10012587007028	7	28	7/0.127	0.38	0.76	1.90	0.76	0.61	7.72	7.42
10012587007026	7	26	7/0.16	0.48	0.76	2.00	0.76	0.61	8.03	7.73
10012587007024	7	24	11/0.16	0.61	0.76	2.13	0.76	0.61	7.91	7.61
10012587007022	7	22	17/0.16	0.76	0.76	2.28	0.76	0.61	8.36	8.06
10012587007020	7	20	26/0.16	0.95	0.76	2.47	0.76	0.61	8.93	8.63
10012587007018	7	18	41/0.16	1.44	0.76	2.76	0.76	0.61	9.8	9.5
10012587007016	7	16	26/0.254	1.84	0.76	3.07	0.76	0.61	10.73	10.43
10012587007014	7	14	41/0.254	2.29	0.76	3.46	0.76	0.61	11.9	11.6
10012587007012	7	12	65/0.254	3.05	0.76	3.95	0.76	0.61	13.37	13.07
10012587007010	7	10	105/0.25 4	3.6	0.76	5.00	0.76	0.61	16.52	16.22
10012587007008	7	8	168/0.25 4	4.6	1.15	6.6	1.53	1.22	22.86	22.24