

Specifications of UL1061 Series Hook Up Cable

Part No.	Conductor Type	Conductor			Insulation		Conductor Resistance Max (Ω /km)	Insulation Resistance Min ($M \Omega .Km$)	Withstanding Voltage (V)
		AWG	Wire No./mm	O.D. mm	Thickness (mm)	O.D. (mm)			
1001106130 S7	Stranded	30	7/0.10	0.30	0.23	0.80	354.24	15	2000
1001106128 S7		28	7/0.127	0.38	0.23	0.88	223.75		
1001106126 S7		26	7/0.16	0.48	0.23	0.98	139.73		
1001106124 S11		24	11/0.16	0.61	0.23	1.11	93.3		
1001106122 S17		22	17/0.16	0.76	0.23	1.26	55.0		
1001106120 S26		20	26/0.16	0.94	0.23	1.54	34.6		
1001106118 S41		18	41/0.16	1.18	0.23	1.84	21.8		
1001106116 S26		16	26/0.25 4	1.49	0.23	2.20	13.7		
1001106102 8S1	Solid	28	1/0.32	0.32	0.23	0.82	227.39		
1001106102 6S1		26	1/0.404	0.40 4	0.23	0.90	142.79		
1001106102 4S1		24	1/0.511	0.51 1	0.23	1.01	89.39		
1001106102 2S1		22	1/0.643	0.64 3	0.23	1.14	54.3		
1001106102 0S1		20	1/0.813	0.81 3	0.23	1.41	33.9		
1001106101 8S1		18	1/1.024	1.02 4	0.23	1.68	21.4		
1001106101 6S1		16	1/1.31	1.31	0.23	1.99	21.4		