

Specification

Part No.	Conductor Type	Conductor			Insulation		Spiral		Jacket		Conductor Resistance Ω /km	Min Insulation Resistance $M \Omega .Km$	Voltage Resistance V
		AWG	Wire No./mm	O.D. mm	Thickness mm	O.D. mm	Size mm	O.D. mm	Thickness mm	O.D. mm			
1001153330	Stranded	30	7/0.10	0.30	0.23	0.80	0.10	1.00	0.30	1.66	354.24	15	1500
1001153328		28	7/0.127	0.38	0.23	0.88	0.10	1.08	0.30	1.74	223.75		
1001153326		26	7/0.16	0.48	0.23	0.98	0.10	1.18	0.30	1.84	139.73		
1001153324		24	11/0.16	0.61	0.23	1.11	0.10	1.31	0.30	2.01	93.3		
1001153322		22	17/0.16	0.76	0.23	1.26	0.10	1.56	0.30	2.16	55.0		
1001153320		20	26/0.16	0.94	0.23	1.64	0.10	1.84	0.30	2.54	34.6		
1001153318		18	41/0.16	1.18	0.23	1.98	0.12	2.22	0.30	2.92	21.8		
1001153316		16	26/0.254	1.49	0.23	2.29	0.12	2.53	0.30	3.23	13.7		