

Specifications

Part No.	Conductor			Insulation			Shield		Jacket		Resistance
	AWG	NO./mm	O.D.	Cores	Thickness	O.D.	Warp	Braiding	Thickness	O.D.	
100121143002030	30	7/0.10	0.30	2	0.25	0.80	AL	16/4/0.10	0.76	3.52	319.26
100121143003030	30	7/0.10	0.30	3	0.25	0.80	AL	16/4/0.10	0.76	3.64	319.26
100121143004030	30	7/0.10	0.30	4	0.25	0.80	AL	16/4/0.10	0.76	3.85	319.26
100121143005030	30	7/0.10	0.30	5	0.25	0.80	AL	16/4/0.10	0.76	5.42	319.26
100121143002028	28	7/0.127	0.38	2	0.25	0.88	AL	16/4/0.10	0.76	3.68	197.94
100121143003028	28	7/0.127	0.38	3	0.25	0.88	AL	16/4/0.10	0.76	3.82	197.94
100121143004028	28	7/0.127	0.38	4	0.25	0.88	AL	16/4/0.10	0.76	4.05	197.94
100121143005028	28	7/0.127	0.38	5	0.25	0.88	AL	16/4/0.10	0.76	4.30	197.94
100121143002026	26	7/0.16	0.48	2	0.25	0.95	AL	16/4/0.10	0.76	3.82	124.71
100121143003026	26	7/0.16	0.48	3	0.25	0.95	AL	16/4/0.10	0.76	3.97	124.71
100121143004026	26	7/0.16	0.48	4	0.25	0.95	AL	16/4/0.10	0.76	4.21	124.71
100121143005026	26	7/0.16	0.48	5	0.25	0.95	AL	16/4/0.10	0.76	4.49	124.71
100121143002024	24	11/0.16	0.61	2	0.25	1.10	AL	16/5/0.10	0.76	4.12	98.54
100121143003024	24	11/0.16	0.61	3	0.25	1.10	AL	16/5/0.10	0.76	4.29	98.54
100121143004024	24	11/0.16	0.61	4	0.25	1.10	AL	16/5/0.10	0.76	4.58	98.54
100121143005024	24	11/0.16	0.61	5	0.25	1.10	AL	16/5/0.10	0.76	4.89	98.54
100121143002022	22	17/0.16	0.76	2	0.25	1.26	AL	16/5/0.10	0.76	4.45	51.35
100121143003022	22	17/0.16	0.76	3	0.25	1.26	AL	16/5/0.10	0.76	4.63	51.35
100121143004022	22	17/0.16	0.76	4	0.25	1.26	AL	16/5/0.10	0.76	4.96	51.35
100121143005022	22	17/0.16	0.76	5	0.25	1.26	AL	16/5/0.10	0.76	5.32	51.35

