

Specifications

Part No.	Cores	Conductor			Insulation		Jacket		O.D.	
		AWG	N0./mm	O.D. (mm)	Thickness (mm)	O.D. (mm)	Max. Thickness (mm)	Min. Thickness (mm)	Max. O.D. (mm)	Min. O.D. (mm)
100125860020 26	2	26	7/0.16	0.48	0.76	2.00	0.76	0.61	5.92	5.62
100125860020 24	2	24	11/0.16	0.61	0.76	2.13	0.76	0.61	6.18	5.88
100125860020 22	2	22	17/0.16	0.76	0.76	2.28	0.76	0.61	6.48	6.18
100125860020 20	2	20	26/0.16	0.95	0.76	2.47	0.76	0.61	6.86	6.56
100125860020 18	2	18	41/0.16	1.44	0.76	2.76	0.76	0.61	7.04	6.74
100125860020 16	2	16	26/0.25 4	1.84	0.76	3.07	0.76	0.61	7.66	7.36
100125860020 14	2	14	41/0.25 4	2.29	0.76	3.46	0.76	0.61	8.44	8.14
100125860020 12	2	12	65/0.25 4	3.05	0.76	3.95	0.76	0.61	9.42	9.12
100125860020 10	2	10	105/0.2 54	3.6	0.76	5.00	0.76	0.61	11.52	11.22
100125860020 08	2	8	168/0.2 54	4.6	1.15	6.6	0.76	0.61	14.72	14.22
100125860030 26	3	26	7/0.16	0.48	0.76	2.00	0.76	0.61	5.92	5.62
100125860030 24	3	24	11/0.16	0.61	0.76	2.13	0.76	0.61	6.18	5.88
100125860030 22	3	22	17/0.16	0.76	0.76	2.28	0.76	0.61	6.48	6.18
100125860030 20	3	20	26/0.16	0.95	0.76	2.47	0.76	0.61	6.86	6.56
100125860030 18	3	18	41/0.16	1.44	0.76	2.76	0.76	0.61	7.47	7.17
100125860030 16	3	16	26/0.25 4	1.84	0.76	3.07	0.76	0.61	8.14	7.84
100125860030 14	3	14	41/0.25 4	2.29	0.76	3.46	0.76	0.61	8.98	8.68
100125860030 12	3	12	65/0.25 4	3.05	0.76	3.95	0.76	0.61	10.03	9.78
100125860030 10	3	10	105/0.2 54	3.6	0.76	5.00	0.76	0.61	12.19	11.99

100125860030 08	3	8	168/0.2 54	4.6	1.15	6.6	0.76	0.61	15.74	15.44
100125860040 28	4	28	7/0.127	0.38	0.76	1.90	0.76	0.61	6.30	6.00
100125860040 26	4	26	7/0.16	0.48	0.76	2.00	0.76	0.61	6.54	6.24
100125860040 24	4	24	11/0.16	0.61	0.76	2.13	0.76	0.61	6.67	6.37
100125860040 22	4	22	17/0.16	0.76	0.76	2.28	0.76	0.61	7.04	6.74
100125860040 20	4	20	26/0.16	0.95	0.76	2.47	0.76	0.61	7.49	7.19
100125860040 18	4	18	41/0.16	1.44	0.76	2.76	0.76	0.61	8.19	7.89
100125860040 16	4	16	26/0.25 4	1.84	0.76	3.07	0.76	0.61	8.94	8.64
100125860040 14	4	14	41/0.25 4	2.29	0.76	3.46	0.76	0.61	9.87	9.58
100125860040 12	4	12	65/0.25 4	3.05	0.76	3.95	0.76	0.61	11.1	10.8
100125860040 10	4	10	105/0.2 54	3.6	0.76	5.00	0.76	0.61	13.59	13.29
100125860040 08	4	8	168/0.2 54	4.6	1.15	6.6	0.76	0.61	17.46	17.16
100125860050 28	5	28	7/0.127	0.38	0.76	1.90	0.76	0.61	6.82	6.52
100125860050 26	5	26	7/0.16	0.48	0.76	2.00	0.76	0.61	7.08	6.78
100125860050 24	5	24	11/0.16	0.61	0.76	2.13	0.76	0.61	7.28	6.98
100125860050 22	5	22	17/0.16	0.76	0.76	2.28	0.76	0.61	7.68	7.38
100125860050 20	5	20	26/0.16	0.95	0.76	2.47	0.76	0.61	8.19	7.89
100125860050 18	5	18	41/0.16	1.44	0.76	2.76	0.76	0.61	8.98	8.68
100125860050 16	5	16	26/0.25 4	1.84	0.76	3.07	0.76	0.61	9.81	9.51
100125860050 14	5	14	41/0.25 4	2.29	0.76	3.46	0.76	0.61	10.87	10.57
100125860050 12	5	12	65/0.25 4	3.05	0.76	3.95	0.76	0.61	12.19	11.89
100125860050 10	5	10	105/0.2 54	3.6	0.76	5.00	0.76	0.61	15.02	14.72

10012586005008	5	8	168/0.254	4.6	1.15	6.6	0.76	0.61	19.34	19.04
10012586006028	6	28	7/0.127	0.38	0.76	1.90	0.76	0.61	7.29	6.99
10012586006026	6	26	7/0.16	0.48	0.76	2.00	0.76	0.61	7.57	7.27
10012586006024	6	24	11/0.16	0.61	0.76	2.13	0.76	0.61	7.91	7.61
10012586006022	6	22	17/0.16	0.76	0.76	2.28	0.76	0.61	8.36	8.06